

U.S. Patent Application Serial No. 10/788,664
Reply to Office Action dated December 6, 2005

Amendments to the Claims:

This listing of claims will replace all prior versions and listings of claims in the application:

Listing of Claims:

1. (Currently Amended) Apparatus for measuring the instantaneous distance between the stern of a vessel (A) and a fixed structure (B, C) such as a quay, jetty, landing stage or the like, during a reversing operation for docking alongside the said fixed structure, including comprising:

- a plurality of transmitter-receiver means (10, 20) for emitting acoustic signals in the form of beams (F1, F2) rearwardly from the stern and for receiving acoustic signals reflected by the fixed structure (B, C), wherein the number of transmitter-receiver means and the angle of aperture of the respective beams are such that their overall field of view includes substantially all the area behind the stern, and wherein each transmitter-receiver includes transducer means operable to convert first input electrical signals into output acoustic signals and to convert reflected acoustic signals into second electrical signals to supply to electronic processing means;
- electronic processing means coupled electrically to the transmitter-receiver means for

supplying the said first electrical signals cyclically to the said transducer means,

receiving the said second electrical signals converted from reflected acoustic signals, and

determining the instantaneous distance between the vessel and the fixed structure on the basis of first and second electrical signals;

U.S. Patent Application Serial No. 10/788,664
Reply to Office Action dated December 6, 2005

- visual and/or acoustic signalling means coupled to the electronic processing means for producing a visual and/or acoustic signal in real time indicating the determined instantaneous distance;

at least one first long-range transmitter-receiver unit for emitting a first output acoustic signal in the form of a beam with a range of around 7-15 metres;

at least one second short-range transmitter-receiver unit for emitting an output acoustic signal in the form of a beam with a beam angle greater than 20° and preferably of around 60-120°;

wherein the plurality of transmitter-receiver means comprise:

a plurality of first long-range transmitter-receiver units, mounted aligned in at least one longitudinal vertical plane on the stern of the vessel, so as to direct rearwardly a corresponding plurality of first conical beams with substantially horizontal axes, parallel to one another in at least one longitudinal vertical plane;
and

a plurality of second short-range transmitter-receiver units mounted on the stern of the vessel and aligned in a horizontal plane so as to direct a corresponding plurality of second conical beams with substantially horizontal axes, parallel to one another in at least one substantially horizontal plane.

2. (Cancelled)

3. (Currently Amended) Apparatus according to ~~Claim 2, in which~~ Claim 1, wherein the said first transmitter-receiver unit (10) is operable to emit a first output acoustic signal in the form of a beam (F1) with a narrow beam angles (α), of around 8-20°.

U.S. Patent Application Serial No. 10/788,664
Reply to Office Action dated December 6, 2005

4. (Cancelled)

5. (Currently Amended) Apparatus according to ~~Claim 4, in which~~ Claim 1, wherein the said second transmitter-receiver unit (20) is operable to emit a second output acoustic signal in the form of a beam (F2) with a short-range of around 1-2 metres.

6-7. (Cancelled)

8. (Currently Amended) Apparatus according to ~~Claim 7~~ Claim 1, wherein the first long-range transmitter-receiver units (10) are mounted aligned in a longitudinal vertical plane passing through the centre line of the vessel.

9. (Currently Amended) Apparatus according to ~~Claim 7~~ Claim 1, wherein the second short-range transmitter-receiver units (20) are mounted to the side of the first units (10).

10. (Currently Amended) ~~Apparatus according to Claim 6, including:~~

Apparatus for measuring the instantaneous distance between the stern of a vessel and a fixed structure such as a quay, jetty, landing stage or the like, during a reversing operation for docking alongside the fixed structure, the apparatus comprising:

a plurality of transmitter-receiver means for emitting acoustic signals in the form of beams rearwardly from the stern and for receiving acoustic signals reflected by the fixed structure, wherein the number of transmitter-receiver means and the angle of aperture of the respective beams are such that their overall field of view includes substantially all the area behind the stern, and wherein each transmitter-receiver includes transducer means operable to convert first input electrical signals into output acoustic signals and to convert reflected acoustic signals into second electrical signals to supply to electronic processing means;

U.S. Patent Application Serial No. 10/788,664
Reply to Office Action dated December 6, 2005

electronic processing means coupled electrically to the transmitter-receiver means
for

supplying the first electrical signals cyclically to the transducer means,

receiving the second electrical signals converted from reflected acoustic signals,

and

determining the instantaneous distance between the vessel and the fixed structure
on the basis of first and second electrical signals;

visual and/or acoustic signalling means coupled to the electronic processing
means for producing a visual and/or acoustic signal in real time indicating the determined
instantaneous distance;

at least one first long-range transmitter-receiver unit for emitting a first output
acoustic signal in the form of a beam with a range of around 7-15 metres; and

at least one second short-range transmitter-receiver unit for emitting an output
acoustic signal in the form of a beam with a beam angle greater than 20° and preferably
of around 60-120°;

- at least one short-range transmitter-receiver unit ~~(20)~~ mounted on the stern of the vessel for directing at least one second output acoustic signal rearwardly in the form of a beam ~~(F2)~~ with a beam angle ~~(β)~~ greater than 20° along a rearward longitudinal path, and

- a first and a second series of first long-range transmitter-receiver units ~~(10)~~, mounted on the stern of the vessel aligned in two longitudinal vertical planes, to either side of the second unit ~~(20)~~ so as to direct rearwardly two corresponding series of first

U.S. Patent Application Serial No. 10/788,664
Reply to Office Action dated December 6, 2005

- conical beams (F1) with substantially horizontal axes, parallel to one another in the said longitudinal vertical planes.
11. (Currently Amended) Apparatus according to ~~Claim 2~~ Claim 1, including:
- a first series of long-range transmitter-receiver units (10) mounted on the stern of the vessel and spaced vertically, and
- a second series of long-range transmitter-receiver units (10) mounted on the stern of the vessel and spaced laterally.
12. (Currently Amended) Apparatus according to Claim 11, including:
- a first series of long-range transmitter-receiver units (10) aligned along a central longitudinal vertical plane, and
- a second series of long-range transmitter-receiver units (10) aligned in a horizontal plane.
13. (Currently Amended) Apparatus according to Claim 1, wherein the transmitter-receiver units include at least one transmitter-receiver (10, 20) operable to emit an output acoustic signal in the form of a conical beam (F1, F2).
14. (Currently Amended) Apparatus according to Claim 1, wherein the transmitter-receiver units include at least one transmitter-receiver (10, 20) operable to emit an output acoustic signal in the form of a beam (F1, F2) with different beam angles in the vertical plane from the horizontal plane.
15. (Currently Amended) Apparatus according to Claim 14, in which the transmitter-receiver units include at least one long-range transmitter-receiver unit (10) operable to emit an acoustic signal in the form of a beam (F1) with a wider beam angle in a vertical plane and a narrower beam angle in a horizontal plane.

U.S. Patent Application Serial No. 10/738,664
Reply to Office Action dated December 6, 2005

16. (Currently Amended) Apparatus according to Claim 1, wherein the transmitter-receiver units ~~(10, 20)~~ are operable to emit acoustic signals in the form of beams ~~(F1, F2)~~ in configuration which is symmetrical relative to a longitudinal vertical plane passing through the centreline of the vessel.